



Underwriters Laboratories Inc.®

File E67774
Project 01SC02550

March 2, 2001

REPORT
ON
COMPONENT - SPECIAL-USE SWITCH

Shin Chin Industrial Co., Ltd.
Tainan Hsien, Taiwan

Copyright © 2001 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce that portion of this Report consisting of this Cover Page through Page 4.

DESCRIPTION

PRODUCT COVERED:

USR, CNR: Component, Special-Use Switches.

Cat. No.	Elec. Rating	Temp.	POL/	PP	ENDUR	SPCOA
	A-V-F-HP	(°C)	THR			
R13-508 f/b A, B AL or BL	3-125-60 1.5-250-60	85	1/1	6K	-	

GENERAL:

The devices are push on-off type switches with solder terminals. The differences between the models are the standard or momentary type and with or without a LED. All other parts are identical. The LED has no function, it is either permanently on or off, or controlled by a different source.

EXPLANATION OF PRODUCT COVERED TABLE:

Abbreviations (if used)

f/b	followed by
ww/o	with or without
Res.	Resistive load. 98-100 percent power factor.
POL/THR	No. of Poles/No. of Throws. "M" stands for Multi-Pole or Multi-Throw, e.g. 2/M indicates 2 Pole, Multi-Throw.
PP	"PP" stands for Per Pole. PP in this column indicates that each pole is capable of switching the rated current.
ENDUR	Endurance Rating
SPCOA	Special Conditions of Acceptability; the applicable special COAs are indicated in this column in number form. The corresponding COAs are given in the following page.