







PB05



Rating: 3A 125 VAC
1.5A 250 VAC
Contact Resistance: 100mΩ Max.
Insulation Resistance:DC 500V 100MΩ Min.
Dielectric Strength:AC 1000V 1 minute
Total travel:1.4±0.4mm
Operating Force:200±50gf
Mechanical Life: Over 30,000 cycles
Electrical Life: Over 10,000 cycles
Operating Temperature:-20°C~+70°C
Soldering Temperature:256°C for 5 Seconds
Function: OFF - (ON)
Welding method:Manual Soldering
(350°C±5°C, 3s±0.5s)

FUNCTION

CUT-OUT



2P SPST

Panel Thickness: 3mm MAX.

Y	Yellow	黄色
W	White	白色
U	Blue	蓝色
R	Red	红色
G	Green	绿色
B	Black	黑色
A	Gray	灰色
CAP COLOR (X)		

MATERIAL:

Base: Brass, Chrome or Tin plated ;
Cap: ABS ;
Terminal: Copper, Silver or Tin plated ;
Nut: Brass,Chrome or Tin plated .

			公差 TOLERANCES	角度 ANGLE	单位 DIMENSION	图号
A2	重新整理	2016.12.11	N/A	1°	品名 TITLE	JS-726A
A1	重新整理	2016.06.29	N/A		日期 DATE	姜庆勇
A0	New Issue	2011.12.08	N/A		绘图 DATE	姜庆勇
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	日期 DATE